



**Inline Cable Colour Code**

- 1 Black
- 2 White
- 3 Green

(Bulkhead Leads Number Tagged)

**Material Specifications**

- Connector Body : Neoprene (CR)
- Bulkhead Body : Brass UNS-C36000
- Contacts : Brass UNS-C36000
- Nuts & Washers : Brass UNS-C36000
- Location pin : AISI 303
- 'O' Rings : Nitrile
- Locking Sleeve : Delrin
- Snap Ring : AISI 302
- Inline Cable (60 cm) : 18 AWG 1,0 mm<sup>2</sup> Rubber
- BH Leads (30 cm) : 20 AWG 0,5 mm<sup>2</sup> Teflon
- Options : See index pages

**Connector Specifications**

- Single Contact Rating : 300 V @ 10 Amp
- Connector Rating 2 pins : 300 V @ 10 Amp
- Connector Rating 3 pins : 300 V @ 6 Amp
- Insulation Resistance : >200 megaohm
- Contact Resistance : <0,01 ohm
- Wet Matings : >500
- Temp. Rating : -4° to +60° C  
25° to 140° F
- Depth Rating : 700 bar - 10.000 psi

Dimensions in mm.  
Threads in inches.  
1 inch = 25,4 mm.  
1 mm = 0,03937 inch.

Modification rights reserved

Drawing No. SE 300-52